

Coil Specification (at 20°C)

Coil Sensitivity	Nominal Voltage (VDC)	Nominal Current (mA)	Coil Resistance ($\Omega \pm 10\%$)	Power Consumption (W)	Pull-In Voltage (VDC)	Drop-Out Voltage (VDC)	Maximum Allowable Voltage (VDC)
GSZ	3	176.5	17	Abt. 0.54	80% Maximum	5% Minimum	120%
	5	106.4	47				
	6	88	68				
	9	58	155				
	12	44.4	270				
	24	21.8	1100				
	48	11	4400				

Ordering Information

GSZ - SS - 1 12 D M

Contact Form:

M: One Form A

Coil Type:

D: Standard DC Coil

Coil Voltage: 03: 3V, 05: 5V, 06: 6V, 09: 9V, 12: 12V, 24: 24V, 48: 48V

Number of Pole:

1: One Pole

Type of Sealing:

SS: Flow Solder Type

SH: Plastic Sealed Type

Type:




GSZ

Classification


Model	GSZ
Contact Form	1A
Flow Solder Type	GSZ-SS-1□□DM
Plastic Sealed Type	GSZ-SH-1□□DM

Dimension

GSZ-SS/SH



BOTTOM VIEW



BOTTOM VIEW

Reference Data

